

PRODUCT INFORMATION PAGE

FUGA-FIX

Parquet filler

PROPERTIES:

Professional, light, fast drying liquid binder to be mixed with the wood dust. When dried, the filler adheres to the filled space perfectly. When hardened, the slits filled with FUGA-FIX filler retain the natural wood colour.

APPLICATION:

For filling of damage, slits in parquet prior to lacquer application, luting of indents, scratches in all types of glued parquets and other wooden floors.

FUGA FIX binder can be used under all types of wood lacquers.

GROUND PRIMING:

Mix FUGA-FIX binder with wood dust of the same wood type to obtain a mass suitable for sealing. Apply on the parquet using a smooth stainless long float.

DRYING TIME:

30 - 45 minutes from luting, depending on the ground, room temperature and air humidity. The best conditions for use are: temperature of 18 – 25°C, with relative air humidity of 35 – 65%.

STORAGE:

Store in the originally sealed packaging, in a dry place, in temperature exceeding +5°C.

CONSUMPTION:

70 – 100 ml/m². Efficiency of 1 litre, depending on the slit size, is ca. 12 m².

TECHNICAL DATA:

Form:	liquid
Colour:	colourless
Odour:	specific
Boiling point range:	82 – 122°C
Ignition point:	320°C
Oxidizing properties:	none
Density:	0.83 g/cm ³
Suitable for use:	24 months from production date
Packaging size:	1L, 5L, 10L
Art. no.:	9106

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.