

PRODUCT INFORMATION PAGE

PU-CLEANER

Preparation removing residues of polyurethane glue from wooden floors

PROPERTIES:

Professional preparation for removal of residues resulting from adhesion of ready parquets with polyurethane single- and bi-component glues. It removes the residues of unbound or partially bound glue from wooden floors.

APPLICATION:

Preparation for removal of contamination from parquet setting works. Use up to 3 - 4 hours from contamination.

METHOD OF USE:

Apply the preparation on a clean cloth and wipe the surface removing the glue residues from the floor.

INSTRUCTIONS:

Keep away from children.

NOTE:

In case of parquets coated with aqueous or acrylic lacquer, it is recommended to perform a lacquer resistance trial due to their low strength.

CONSUMPTION:

from 45m² – 170m²

SUITABLE FOR USE:

24 months from the production date provided on the packaging

STORAGE:

Store in the originally sealed packaging, in temperature exceeding 0°C.

TECHNICAL DATA:

Form:	liquid
Colour:	brown
Odour:	weak
Density:	0,95 g/cm ³
Ignition point:	75 °C
Initial boiling point and boiling range:	184 °C – 193 °C
Water solubility:	very good

PACKAGING SIZE: 1L

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.