

## PRODUCT INFORMATION PAGE

# RENO-DECK

---

### IMPREGNATING-SEALING POLYMER COATING FOR DECKING BOARDS

---

- Protects surface against becoming grey;
- Protects against acid rain;
- Ensures UV protection;
- Protects against snow and salt;

**PROPERTIES:**

Reno-Deck is a special, colorless polymer that allows for filling micropores of wood. It forms an impregnating and sealing coating. The product is hydrophobic, which prevents water from leaching out the applied oil. It reduces the need for regular care and makes cleaning easier. Use on oiled or untreated decking boards.

**PURPOSE:**

For terraces made of wood, including such exotic wood as Siberian larch, bangkirai, massaranduba, as well as for gazebos, pergolas, wooden facades and others.

**INSTRUCTIONS:**

The surface must be dry, clean and dusted. Any old coatings must be removed. We recommend to try it in a less-visible place first. Apply at the temperature of +5°C to +25°C. Before use, add a coat of Tung oil (Wood Oil T) to wood, to protect it against cracking and drying. Leave it to dry for ca. 24 hours. Remove excess oil with a cloth or a paper towel. We recommend to apply 3 layers of RENO-DECK using a brush, with 30 minutes between coats. Avoid using the polymer, if there is a risk of rain. Expected durability of the coating: 1-2 years.

**PACKAGE SIZE:** 1L, 5L

**STORAGE:**

The product should be stored in the unopened, original packaging in a dry and cool area at a temperature of +5°C to +25°C

**EFFICIENCY:** 8-10 m<sup>2</sup>/1L

**CURING TIME:**

Depending on the temperature, relative air humidity and the species of wood, ca. 30-60 minutes.

**EXPIRATION:**

12 months from the production date on the packaging.

**SPECIFICATIONS:**

Form:	Liquid
Colour:	Colourless
Smell:	Distinctive
Boiling point range:	+82°C - +122°C
Flash point:	320°C
Oxidizing properties:	absent
Density:	0.81g/cm <sup>3</sup>

---

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.