

PRODUCT INFORMATION PAGE

RENOPRIMER AQUA

Multifunctional primer

- solvent free
- can be diluted with water
- upon modifications can feature as electric conductor.

Properties and Application:

Universal and multifunctional primer on the base of synthetic dispersion. Improves adhesion, closing pores on the porous and non-porous subfloors. Recommended on variety of subfloors as concrete, screeds, USB boards, ceramic boards, natural stone, synthetic stones. Can be used as an activator – adhesion agent for self-levelling and screed coating.

Priming:

The subfloor has to be solid, free from cracks, dry, and clean. The screed subfloor has to be polished and clean. The primer should be applied by the roller evenly. Avoid creating excess and paddles. Can be diluted with water in 1:1 ratio. (In case of the very porous subfloors 1:3 ratio)

Storage:

Renoprimer Aqua must be kept in original packaging in cool and dry place. **Keep away from frozen conditions.** Follow the instructions given in this chart.

Shelve life:

6 months from the production date in original and closed package.

Technical data/ description:

Base – synthetic dispersion

Colour – white

Density – 1.0g/cm³

Workability temperature - $\geq 10^{\circ}\text{C}$

Recommended tools – brush or roller

Coverage – about 75g/m³ (at 1;1 ratio)

Packaging – 5kg, 10kg, 20kg.

Accordingly to the current regulations, this product does not contain ingredients/components classified as harmful.

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.