

## PRODUCT INFORMATION PAGE

# RENOVACOL PU-112-R

---

### Thinner mixture

---

**PROPERTIES:**

Thinner mixture for the polyurethane primer Renoprimer PU-112.

**APPLICATION:**

For use before adherence of parquets with URETAX - 2k on absorptive and non-absorptive grounds with increased residual moisture.

**METHOD OF USE:**

Apply on dry surfaces free from contamination, traces of moisture. Apply evenly using a roller or brush. The first layer must be applied using thinner RENOVACOL PU-112 R, adding 20% to 40%. The second layer must be applied after 10 hours. Adherence of parquet can be commenced after 5-7 hours from priming. In order to improve adherence of the ground to the glue, the last wet layer of the ground must be covered with quartz sand (from 0.3 to 1 mm).

**TECHNICAL DATA:**

Form:	liquid
Colour:	transparent light brown
Odour	weak
Solubility:	thinner
Drying time:	1.5 to 2 hours
Stepping on allowed:	after 2-3 hours
Ford viscosity cup:	4mm /(ISO2431) ca. 15 seconds
Art. no.	R 0946

**CONSUMPTION:**

Concrete ground priming from 0.2 - 0.5 l/m<sup>2</sup>

**STORAGE:**

Store in the originally sealed packaging, in a dry place, in temperature exceeding +50C.

**INSTRUCTIONS:**

Store in the originally sealed packaging in temperature exceeding +50C. In case of long-term storage, mix the preparation before use.

**SUITABLE FOR USE:**

24 months from production date

**VOLUME:**

packaging 5L, 10L.

---

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.