

PRODUCT INFORMATION PAGE

WOOD OIL T

Terrace oil

PROPERTIES:

WOOD OIL T is a new reliable formula of natural tung oil with velvet coating for external wood impregnation. Emphasises the natural wood beauty. Prevents greying, drying and cracking of wood. Penetrates deep into the wood, securing it effectively against destructive impact of atmospheric conditions: water, humidity, snow. Resistant to UV radiation.

APPLICATION:

For impregnation of terraces, arbours, furniture as well as facades made of sliding panels, from domestic and exotic wood, both soft and hard.

PREPARATION:

The wooden surfaces must be dry, clean, free from dust and other contamination. Wood humidity cannot exceed 18%. Air humidity from 40% - 60%.

METHOD OF USE:

Mix before use. Apply evenly using a roller or brush in temperature from 15oC to 25oC. Do not apply oil in case of risk of rain within 24 hours. Spread the oil surplus and add some more in the most absorptive places. Apply until surface saturation.

NOTE: Self-combustion risk. For cloths soiled with oil, it is recommended to immerse them in water or place in a metal tightly closed container.

DRYING TIME: ca. 24 hours. The drying time depends on temperature and relative air humidity as well as wood grade.

CONSUMPTION: 100 – 120 ml/m². 1 litre efficiency 8 – 10 m². Consumption depending on the wood grade and saturation level.

STORAGE: Store in the originally sealed packaging, in a dry place, in temperature exceeding +50 °C.

TECHNICAL DATA:

Form:	liquid
Colour:	straw yellow
Odour:	specific Boling
Point range:	187- 213 °C
Ignition point:	60 °C
Oxidizing properites:	none
Density:	0,78 g/cm ³
Suitable for use:	24 months from production date
Packaging size:	2, 5 L
Art. no.:	0967

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.