

PRODUCT INFORMATION PAGE

LVT Dryback

ADHESIVE FOR LVT DRYBACK AND TILES

PROPERTIES

Low-emission, fibre-reinforced, polymer dispersion-based LVT Dryback adhesive. Excellent adhesion and a short pre-curing time. Prevents shrinkage of vinyl panels. Does not contain solvents. For indoor use.

APPLICATION:

Adhesive with high initial bonding strength for laying all panels, LVT tiles, soft and hard PVC flooring, rubber flooring up to 4 mm in rolls, carpet flooring with jute and latex backings. It is designed for industrial and commercial applications. Wet application adhesive. Can be used on underfloor heating. For extreme loads, the use of Renove single-component hybrid adhesive is recommended.

SURFACE PREPARATION:

The LVT adhesive is designed for use on absorbent, filler-coated mineral substrates. The substrate must be dry, strong and stable, free from dust and other contamination. Any residues that affect the adhesion of the product must be removed. Remove cement and anhydrite laitance by grinding, brushing.

METHOD OF USE

Mix before use. Apply with a notched spreader or a roller.

TECHNICAL DATA:

Basis:	polymer dispersion
Colour:	white
Density:	1.25g/cm
Waiting time:	approx. 10 min.
Open time:	approx. 30 min.
Load:	pedestrian traffic after approx. 3-4 hours full load after approx. 48 hours
Pointing:	after 24 hours
Application:	Apply in substrate temperature above 15°C, with relative humidity below 65%
Consumption:	low consumption: 200-300 g/m ² depending on the substrate type, material used and applied A1 or A2 mortar,
Cleaning:	uncured adhesive - water, cured - acetone
Packaging:	4kg, 12kg plastic bucket

STORAGE:

12 months in original, sealed packaging at +10°C + 20°C. Protect from frost.

According to current legislation, the product does not contain chemicals classified as hazardous to health.

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.

Renove sp. z o.o. / Wola Pękoszewska 82A / 96-111 Kowiesy
tel. +48 46 831 74 14 / fax: +48 46 834 99 62 / www.renove.com.pl